

ARTECH SYSTEMS

Stepline Original Specification

Stepline Original is a rubber composite material that is used to provide a hardwearing slip resistant surface in floor/step areas and is suitable for internal and external applications. It can be cast in-situ using the dovetail section in concrete or terrazzo, laid with the flooring material – usually ceramic or stone, or fitted retrospectively in a prepared groove in wood, stone or other surfaces (please check with our technical dept). Stepline can also be laid as a floor finish using an adhesive suitable for the application.

Recommended Adhesives

Internal & External – Grip240 Cartridge Applied Adhesive

Recommended Substrates

Concrete, stone, marble, terrazzo, ceramic, wood, steel

Size – Stock Lengths (mm)

Max width: 2750(l) x 250(w) x 8, 6 or 4(d)

Min width: 2750(l) x 10(w) x 8, 6 or 4(d)

Cut lengths are available to specification

25mm, 38mm, 50mm diameter discs

Finish

The finished surface of Stepline is scoured.

Colours

Black, White, Grey, Brown, Yellow.

Codes

LL(xx/x) Square Section

SS(xx/x) Dovetail Section

DC(xx/x) Disc Section

BB(xx/x) Bullnose Section

LONDON

47 Gee Street
Clerkenwell
London EC1V 3RS

01592 630 030
london@durafloor.com

LEEDS

Vitality House
Milford Place
Leeds LS4 2BQ

0113 243 2131
leeds@durafloor.com

SCOTLAND

Unit 14 Faraday Road
Glenrothes
KY6 2RU

01592 630 030
uksales@durafloor.com