

TREADLINE

Heavy Duty Stair Nosings

NBS SPECIFICATION

M50 RUBBER/ PLASTICS/ CORK / LINO / CARPET TILING

75 /750 /550 STAIR NOSINGS AND TRIMS

PRODUCT REF: TREADLINE NOSINGS

Complete with tread and riser inserts cut to length.
Can be pre-drilled and countersunk for M5 screws.
Screws and plastic plugs supplied on request.

ALUMINIUM PROFILE

- Anodised quality, mill finished extruded aluminium alloy (6063) hardened to T6. Maximum single length 2500mm.

TREAD INSERTS

- A composite of various grits, including Aluminium Oxide, set in cured epoxy. Standard colours: Yellow, White, Black. Others available subject to order quantity
- Slip Resistance Data: - Assessed against UK Slip Resistance Group guidelines for the potential of slipping for people on a flooring material
- Tested using the Pendulum /4S method
- Result: Extremely low potential for slip in dry and wet conditions
- Average surface roughness (Rz values) = 86-90 μm

RISER INSERTS

- UV stabilised PVC
- Standard colours: Yellow, White, Black. Others available subject to order quantity

MANUFACTURER:

Artech Systems, Unit 14 Faraday Road, Southfield Business Park,
Glenrothes, KY6 2RU. Tel 01592 809 900.

Email: sales@artechsystems.co.uk

Website: www.artechsystems.co.uk